



## PRO-OUT4TLS-V2

Custom Pro 4 x HDMI /  
HDBase™ CSC Output Board

### Key Features

- Advanced HDBase™ technology offering distribution of video and audio over a single CAT cable
- Features 4 x simultaneous HDMI / HDBase™ outputs for connection to HDMI displays and HDBase™ receivers
- Advanced Colour Space Conversion (CSC) supports HDMI 2.0 18Gbps specification including HDR support
- Supports 4K 60Hz 4:4:4 UHD video up to 40m\*
- Independent down-scaling of video input resolutions up to 4K 60Hz 4:4:4 to the following formats:
  - 1080p 60Hz (for screens that do not support 4K)
  - 4K 60Hz 4:2:0 (for screens that do not support full 4K 60Hz 4:4:4)
- Extends HDMI 1080p video up to 70m
- Supports all known HDMI audio formats including Dolby TrueHD, Atmos and DTS-HD Master Audio transmission
- Supports PoH (PoE) to power Blustream HDBase™ Receivers
- Quick release card module fittings allowing simple population of input and output cards in Custom Pro Matrix Hub
- HDCP 2.2 Support
- To be used with the HEX70CS-RX receivers

*\*For HDMI 2.0 18Gbps video distribution the PRO-OUT4TLS-V2 must be used with a HDMI 2.0 18Gbps Custom Pro input board*

### Compatible Receivers

HEX70CS-RX

HEX100CS-RX

### Description

The PRO-OUT4TLS-V2 output board offers 4 x dual HDBase™ outputs for connection to a HDBase™ receiver and HDMI display per zone.

The PRO-OUT4TLS-V2 utilises CSC technology allowing support of HDMI 2.0 4K 60Hz 4:4:4 (18Gbps) HDCP 2.2 signal distribution up to lengths of 70m (4K to 40m).

The PRO-OUT4TLS-V2 features independent down-scaling of 4K video inputs on the CSC HDBase™ outputs to allow displays only capable of supporting lower video resolutions to receive 4K video while still showing maximum original 4K UHD resolution on the higher-definition displays.

The PRO-OUT4TLS-V2 also features quick release card module fittings allowing simple installation into the Custom Pro Matrix hub.

### Specifications

- **Video Output Connectors:** 4 x HDMI Type A, 19-pin, female, 4 x HDBase™ RJ45 connector
- **Dimensions Including Connections (W x H x D):** 202mm x 22mm x 188mm
- **Shipping Weight:** 0.5kg
- **Operating Temperature:** 32°F to 104°F (0°C to 40°C)
- **Storage Temperature :** -4°F to 140°F (-20°C to 60°C)