

4K HDMI 2.0 Input Boards



PRO-IN2HAB

Custom Pro 2 x HDMI 2.0 Input Board

Key Features

- Features 2 x HDMI 2.0 inputs which can be independently routed to video output cards
- Supports HDMI 2.0 18Gbps specification including HDR support
- Supports up to 4K UHD 60Hz 4:4:4
- Supports all known HDMI audio formats including Dolby TrueHD, Atmos and DTS-HD Master Audio transmission
- Each HDMI input includes an independent fixed level 2ch analogue audio breakout allowing connection to a local third party audio solution (supports 2ch PCM)
- Quick release card module fittings allowing simple population of input and output cards in Custom Pro Matrix Hub
- HDCP 2.2 Support

**For HDMI 2.0 18Gbps video distribution the PRO-IN2HAB must be used with a HDMI 2.0 18Gbps Custom Pro output board*

Description

The PRO-IN2HAB board features 2 x HDMI 2.0 inputs supporting 4K 60Hz 4:4:4 that can be independently routed to any HDMI / HDBaseT output board. Each HDMI input includes an independent fixed level 2ch analogue audio breakout and features quick release card module fittings allowing simple installation into the Custom Pro Matrix hub.

Specifications

- **Video Input Connectors:** 2 x HDMI Type A, 19-pin, female
- **Audio Output Connectors:** 2 x Analogue Left/Right audio (3.5mm stereo jack)
- **Dimensions Including Connections (W x H x D):** 190mm x 22mm x 188mm
- **Shipping Weight:** 0.5kg
- **Operating Temperature:** 32°F to 104°F (0°C to 40°C)
- **Storage Temperature :** -4°F to 140°F (-20°C to 60°C)



PRO-IN4HAB

Custom Pro 4 x HDMI 2.0 Input Board

Key Features

- Features 4 x HDMI 2.0 inputs which can be independently routed to video output cards
- Supports HDMI 2.0 18Gbps specification including HDR support
- Supports up to 4K UHD 60Hz 4:4:4
- Supports all known HDMI audio formats including Dolby TrueHD, Atmos and DTS-HD Master Audio transmission
- Each HDMI input includes an independent fixed level 2ch analogue audio breakout allowing connection to a local third party audio solution (supports 2ch PCM)
- Quick release card module fittings allowing simple population of input and output cards in Custom Pro Matrix Hub
- HDCP 2.2 Support

**For HDMI 2.0 18Gbps video distribution the PRO-IN4HAB must be used with a HDMI 2.0 18Gbps Custom Pro output board*

Description

The PRO-IN4HAB board features 4 x HDMI 2.0 inputs supporting 4K 60Hz 4:4:4 that can be independently routed to any HDMI/HDBaseT™ output board. Each HDMI input includes an independent fixed level 2ch analogue audio breakout and features quick release card module fittings allowing simple installation into the Custom Pro Matrix hub.

Specifications

- **Video Input Connectors:** 4 x HDMI Type A, 19-pin, female
- **Audio Output Connectors:** 4 x Analogue Left/Right audio (3.5mm stereo jack)
- **Dimensions Including Connections (W x H x D):** 190mm x 22mm x 188mm
- **Shipping Weight:** 0.5kg
- **Operating Temperature:** 32°F to 104°F (0°C to 40°C)
- **Storage Temperature :** -4°F to 140°F (-20°C to 60°C)

Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.