



## Introduction

The Atлона **AT-OME-MH21** is a compact, versatile switcher with HDMI and USB-C inputs. It is equipped with features for complete AV integration in huddle rooms and small meeting spaces, including automatic switching and display control, audio de-embedding, and a USB 3.0 hub for video conferencing peripherals or touch displays. Part of the Omega™ Series of integration products for modern AV communications and collaboration, the OME-MH21 is HDCP 2.2 compliant and supports 4K HDR and 4K/60 4:4:4 at HDMI data rates up to 18 Gbps. Additionally, 4K downscaling to 1080p @ 60, 30, or 24 Hz is available when connected to an HD display. The OME-MH21 includes USB 3.0 and USB-C interfaces for two host PCs, plus two USB Type-A ports for peripheral devices such as a camera, microphone, speakerphone, touch-enabled display, or keyboard and mouse.

## Applications

- Huddle rooms and small meeting spaces**  
 The OME-MH21 provides a compact, yet comprehensive and cost-effective integration solution. When installed below a meeting table, the available Pocket™ 3H (AT-PKT-3H) provides convenient tabletop AV and USB cable access for easy BYOD connectivity.
- Video conferencing**  
 This switcher provides interfacing with USB devices for soft codec conferencing, with video and USB switched together between two host PCs. The USB interfacing is also ideal for a touch-enabled display, enabling on-screen control of a PC.

## Key Features

### Two-input AV switcher

- HDMI and USB-C inputs.
- No need to provide an adapter for USB-C to HDMI.

### USB-C input for AV and data<sup>(1)</sup>

- Provides immediate compatibility with laptops and tablets with USB-C ports supporting AV output.
- Allows clutter-free, single cable connectivity to a PC for video conferencing and collaboration.

### Integrated USB 3.0 hub

- USB type B interface for connection to a host PC, plus two USB type A ports for a peripheral device such as a microphone, speakerphone, camera, or touch display. USB-C input is also available for data connection to a host PC.
- Provides an ideal USB integration solution for software video conferencing, and other applications.

### Selectable 4K to 1080p downscaling

- Integrated video processing available for down-converting 4K/UHD @ 60, 30, or 24 Hz to 1080p.
- Ideal for applications with 1080p displays.

### Automatic display control

- Automatically changes display power state based on active or standby mode of the switcher. Control signals to display are transmitted via IP, RS-232, IR, or CEC.
- Embedded, comprehensive selection of display drivers from the Velocity™ System driver database.
- Enables effortless, automated system operation without the need for an external control system.

### Automatic input selection using hot plug detect and video detection technology

- Selects active input when sources are connected or if there is a change in source power status.
- Enables simplified, automatic system operation without user intervention.

### Audio de-embedding

- De-embeds two channel PCM audio and delivers to a balanced, analog audio output.
- Provides direct interfacing into an external audio system.

## Specifications

| Video                            |  |  |
|----------------------------------|--|--|
| Signal                           | HDMI   |  |
| Copy Protection                  | HDCP 2.2   |  |
| Pixel Clock                      | 600 MHz  |  |
| UHD/HD/SD                        | 4096x2160@60/50/30/25/24 Hz<br>3840x2160@60/50/30/25/24 Hz<br>1920x1080p@60/59.9/50/30/<br>29.97/25/24/23.98 Hz<br>1920x1080i@30/29.97/25 Hz<br>1280x720p@60/59.94/50 Hz | 720x576p@50 Hz<br>720x576i@50 Hz<br>640x480p@60/59.96 Hz<br>640x480i@30 Hz     |
| VESA<br>All resolutions are 60Hz | 2560x1600<br>2048x1536<br>1920x1200<br>1680x1050<br>1600x1200<br>1440x900<br>1400x1050<br>1280x1024  | 1280x800<br>1366x768<br>1360x768<br>1152x864<br>1024x768<br>800x600<br>640x480 |
| Scaler <sup>(2)</sup>            | IN   | OUT  |
|                                  | 4K@24 Hz<br>4K@30 Hz<br>4K@60 Hz, 4:2:0  | 1080p@24 Hz<br>1080p@30 Hz<br>1080p@60 Hz (YUV/RGB, 4:4:4)                     |
| USB-C                            | Up to 4K/UHD @ 60 Hz   |  |
| Color Space                      | YUV, RGB   |  |
| Chroma Subsampling               | 4:4:4, 4:2:2, 4:2:0  |  |
| Color Depth                      | 8-bit, 10-bit, 12-bit  |  |
| HDR                              | HDR10, Hybrid-Log Gamma (HLG), and Dolby® Vision™ @ 60 Hz  |  |

| Audio                        |   |   |  |
|------------------------------|---|---|--|
| HDMI<br>Pass-Through Formats | PCM 2.0<br>LPCM 5.1<br>LPCM 7.1                     | Dolby® Digital<br>Dolby Digital Plus™<br>Dolby TrueHD | DTS® Digital Surround™<br>DTS-HD Master Audio™ |
| Bit Rate                     | 24 Mbits/s max                                      |   |  |
| <b>Analog Audio</b>          |   |   |  |
| Format                       | 2-channel stereo                                    |   |  |
| Balanced Output              | +4 dBu, nominal gain; +20 dBu headroom              |   |  |
| Frequency Response           | 20 Hz to 20 kHz, ±0.5 dB                            |   |  |
| Impedance                    | 150 Ω   |   |  |
| Stereo channel separation    | > 90 dB   |   |  |
| THD + N                      | < 0.004% @ 20 Hz to 20 kHz                          |   |  |
| SNR                          | > 94 dB @ 1 kHz, zero clipping @ 0 dBFS, unweighted |   |  |

| USB               |   |
|-------------------|---|
| Compliance        | 3.0   |
| Maximum Data Rate | 5 Gbps <sup>(3)</sup>                       |
| USB-C             | Supports audio, video, device and host data |

| Ethernet                |   |
|-------------------------|---|
| Port                    | 1 x RJ45  |
| Standards and Protocols | HTTPS, Telnet, mDNS   |
| Speeds                  | 10/100/1000 Mbps  |
| Addressing              | DHCP, Static – selectable through rear panel, IP & RS-232 commands, and built-in web server |

| RS-232     |   |
|------------|---|
| Port       | 2 x 3-pin captive screw                       |
| Use        | Device control and configuration              |
| Baud Rates | 2400, 4800, 9600, 19200, 38400, 57600, 115200 |
| Data flow  | Bidirectional                                 |

| IR              |                      |
|-----------------|----------------------|
| Use             | Pass-through control |
| Frequency Range | 30 kHz to 60 kHz     |

| CEC        |   |
|------------|---|
| Port       | HDMI, Type A, 19-pin female                 |
| Triggering | Through IP, RS-232, and built-in web server |

| Resolution / Distance | 4K/UHD - Feet / Meters |   | 1080p - Feet / Meters |    |
|-----------------------|------------------------|---|-----------------------|----|
| HDMI IN/OUT           | 15                     | 5 | 30                    | 10 |
| USB-C                 | 10                     | 3 | 10                    | 3  |

| Buttons and Indicators                              |  |
|---|--|
| <b>Buttons:</b><br>DISPLAY, INPUT<br>IP MODE, RESET | 2 – momentary, tact-type<br>2 – momentary, tact-type |
| <b>Indicators:</b><br>PWR, INPUT<br>IP MODE, RESET  | 3 – LED, green<br>2 – LED, green                     |

| Connectors      |   |
|-----------------|---|
| HDMI IN         | 1 – Type A, 19-pin female                                     |
| USB-C IN        | 1 – USB Type-C v3.1, 24-pin female, AV input (Alternate Mode) |
| HDMI OUT        | 1 – Type A, 19-pin female                                     |
| USB HUB         | 2 – Type A, 4-pin female                                      |
| USB HOST        | 1 – Type B, female  |
| AUDIO OUT       | 1 – 5-pin captive screw, balanced / unbalanced 2-channel      |
| RS-232 / IR OUT | 1 – 4-pin captive screw (bidirectional)                       |
| LAN             | 1 – RJ45, 100Base-T   |
| PWR             | 1 - Barrel connector, locking                                 |

| Environmental           | Fahrenheit                 | Celsius    |
|-------------------------|----------------------------|------------|
| Operating Temperature   | +32 to +122                | 0 to +50   |
| Storage Temperature     | -4 to +140                 | -20 to +60 |
| Operating Humidity (RH) | 20% to 90%, non-condensing |            |

| Power                 |  |
|-----------------------|--|
| Consumption           | Nominal: 17.9 W<br>Idle: 16.8 W                    |
| External Power Supply | 100 - 240 V AC, 50/60 Hz<br>Output: 5 V / 2.6 A DC |

| Dimensions (H x W x D)    | Inches             | Millimeters    |
|---------------------------|--------------------|----------------|
| Unit                      | 1.02 x 8.62 x 5.98 | 26 x 219 x 152 |
| Power Supply (AT-PS-54-L) | 1.22 x 1.97 x 3.17 | 31 x 50 x 80.6 |

| Weight | Pounds | Kilograms |
|--------|--------|-----------|
| Device | 2.15   | 0.975     |

| Certification |             |
|---------------|-------------|
| Device        | CE, FCC     |
| Power Supply  | CE, FCC, UL |

## Accessories

| SKU            | Description                              |
|----------------|--|
| AT-LC-H2H-1M   | LinkConnect HDMI to HDMI 1 Meter Cable   |
| AT-LC-H2H-2M   | LinkConnect HDMI to HDMI 2 Meter Cable   |
| AT-LC-H2H-3M   | LinkConnect HDMI to HDMI 3 Meter Cable   |
| AT-LC-UC2UC-2M | LinkConnect USB-C to USB-C 2 Meter Cable |

## Footnotes

- (1) USB-C port does not support USB device powering.
- (2) Scaler does not support frame rate conversion.
- (3) When USB SuperSpeed (SS) mode is enabled, video output is supported up to 4K @ 30 Hz and the USB data rate is 5 Gbps. If disabled, video output is supported up to 4K @ 60 Hz and data rate is limited to 480 Mbps.