

4K HDMI 2.0 Output Boards



PRO-OUT4H-V2

Custom Pro 4 x HDMI 2.0
Output Board

Key Features

- Features 4 x HDMI outputs for connection to HDMI displays
- Supports HDMI 2.0 18Gbps specification including HDR
- Supports up to 4K UHD 60Hz 4:4:4*
- Supports all known HDMI audio formats including Dolby TrueHD, Atmos and DTS-HD Master Audio transmission
- Quick release card module fittings allowing simple population of input and output cards in Custom Pro Matrix Hub
- HDCP 2.2 Support

**For HDMI 2.0 18Gbps video distribution the PRO-OUT4HTCS must be used with a HDMI 2.0 18Gbps Custom Pro input board*

Description

The PRO-OUT4H-V2 supports HDMI 2.0 4K 60Hz 4:4:4 (18Gbps) with HDCP 2.2, allowing distribution of inputs to four independent displays.

The PRO-OUT4H-V2 also features quick release card module fittings allowing simple installation into the Custom Pro Matrix hub.

Specifications

- Video Output Connectors: 4 x HDMI Type A, 19-pin, female
- Dimensions Including Connections (W x H x D): 190mm x 22mm x 188mm
- Shipping Weight: 0.5kg
- Operating Temperature: 32°F to 104°F (0°C to 40°C)
- Storage Temperature : -4°F to 140°F (-20°C to 60°C)



PRO-OUT2H-V2

Custom Pro 2 x HDMI 2.0
Output Board

Key Features

- Features 2 x HDMI outputs for connection to HDMI displays
- Supports HDMI 2.0 18 Gbps specification including HDR
- Supports up to 4K UHD 60Hz 4:4:4*
- Supports all known HDMI audio formats including Dolby TrueHD, Atmos and DTS-HD Master Audio transmission
- Quick release card module fittings allowing simple population of input and output cards in Custom Pro Matrix Hub
- HDCP 2.2 Support

**For HDMI 2.0 18Gbps video distribution the PRO-OUT2H-V2 must be used with a HDMI 2.0 18Gbps Custom Pro input board*

Description

The PRO-OUT2H-V2 supports HDMI 2.0 4K 60Hz 4:4:4 (18Gbps) with HDCP 2.2, allowing distribution of inputs to two independent displays.

PRO-OUT2H-V2 also features quick release card module fittings allowing simple installation into the Custom Pro Matrix hub.

Specifications

- Video Output Connectors: 2 x HDMI Type A, 19-pin, female
- Dimensions Including Connections (W x H x D): 190mm x 22mm x 188mm
- Shipping Weight: 0.5kg
- Operating Temperature: 32°F to 104°F (0°C to 40°C)
- Storage Temperature : -4°F to 140°F (-20°C to 60°C)