

Custom Pro 4K - Control Boards



PRO-8IR

Custom Pro IR Board

Key Features


- 8 x 5V IR outputs for routed control of local source equipment
- 8 x 5V IR inputs for distribution of IR to compatible Blustream HDBaseT™ receivers
- Quick release card module fittings allowing simple population of input and output cards in Custom Pro Matrix Hub

Specifications

- IR Input ports: 9 x 5V 3.5mm stereo jack
- IR Output ports: 9 x 5V 3.5mm mono jack
- Dimensions Including Connections (W x H x D): 202mm x 22mm x 188mm
- Shipping Weight: 0.5kg
- Operating Temperature: 32°F to 104°F (0°C to 40°C)
- Storage Temperature : -4°F to 140°F (-20°C to 60°C)

Description

The PRO-8IR IR routing board offers 8 x IR outputs for routed control of local source hardware and 8 x IR inputs for distribution of IR to compatible HDBaseT™ receivers. The PRO-8IR also features quick release card module fittings allowing simple installation into the Custom Pro Matrix hub.



PRO-8RS232

Custom Pro RS232 Board

Key Features

- Features 8 x Bi-directional RS-232 ports for serial communication to corresponding Blustream HDBaseT™ zone receivers
- Quick release card module fittings allowing simple population of input and output cards in Custom Pro Matrix Hub

Specifications

- RS-232 serial ports: 8 x 3-Pin Phoenix connector
- Dimensions Including Connections (W x H x D): 190mm x 22mm x 188mm
- Shipping Weight: 0.5kg
- Operating Temperature: 32°F to 104°F (0°C to 40°C)
- Storage Temperature : -4°F to 140°F (-20°C to 60°C)

Description

The PRO-8RS232, RS-232 routing board offers 8 x bi-directional RS-232 ports for serial communication from all input and output locations when used with compatible Blustream HDBaseT™ transmitters & receivers. The PRO-8RS232 also features quick release card module fittings allowing simple installation into the Custom Pro Matrix hub.

Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.