



PRO-IN2H2V

Custom Pro 2 x HDMI
2 x VGA Input Board

Key Features

- Features 2 x HDMI and 2 x VGA inputs which can be independently routed to video output cards
- Supports up to 4K UHD video (3840 x 2160 @30Hz 4:4:4, 4096 x 2160 @24Hz 4:4:4, and 4K @60Hz 4:2:0)
- Supports all known HDMI audio formats including Dolby TrueHD, Atmos and DTS-HD Master Audio transmission
- Quick release card module fittings allowing simple population of input and output cards in Custom Pro Matrix Hub
- HDCP 2.2 Support

Description

The PRO-IN2H2V input board offers 2 x HDMI and 2 x VGA sources that can be independently routed to any HDMI / HDBaseT output board and features quick release card module fittings allowing simple installation into the Custom Pro Matrix hub.

Specifications

- **Video Input Connectors:** 2 x HDMI Type A, 19-pin, female, 2 x VGA
- **Dimensions Including Connections (W x H x D):** 190mm x 22mm x 188mm
- **Shipping Weight:** 0.5kg
- **Operating Temperature:** 32°F to 104°F (0°C to 40°C)
- **Storage Temperature :** -4°F to 140°F (-20°C to 60°C)

Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.