



PRO-8ABV

Custom Pro Audio Breakout Board

Key Features

- Features 8 x HDMI audio breakouts from corresponding video zone outputs to coaxial digital and analogue L/R audio outputs
- Analogue audio outputs include variable line level control (supports 2ch PCM)
- Quick release card module fittings allowing simple population of input and output cards in Custom Pro Matrix Hub

Description

The PRO-8ABV audio breakout board offers 8 x simultaneous coaxial digital and variable line-level analogue L/R audio outputs and features quick release card module fittings allowing simple installation into the Custom Pro Matrix hub.

Specifications

- **Audio Output Connectors:** 8 x RCA (SPDIF), 8 x Analogue Left / Right audio (3.5mm stereo jack)
- **Dimensions Including Connections (W x H x D):** 202mm x 22mm x 188mm
- **Shipping Weight:** 0.5kg
- **Operating Temperature:** 32°F to 104°F (0°C to 40°C)
- **Storage Temperature :** -4°F to 140°F (-20°C to 60°C)



PRO-8AB

Custom Pro Audio Breakout Board

Key Features

- Features 8 x HDMI audio breakouts from corresponding video zone outputs to coaxial digital and analogue L/R audio outputs (no DSP)
- Quick release card module fittings allowing simple population of input and output cards in Custom Pro Matrix Hub

Description

The PRO-8AB audio breakout board offers 8 x simultaneous coaxial digital and analogue L/R audio outputs and features quick release card module fittings allowing simple installation into the Custom Pro Matrix hub.

Specifications

- **Audio Output Connectors:** 8 x RCA (SPDIF), 8 x 3.5mm stereo jack (L/R)
- **Dimensions Including Connections (W x H x D):** 202mm x 22mm x 188mm
- **Shipping Weight:** 0.5kg
- **Operating Temperature:** 32°F to 104°F (0°C to 40°C)
- **Storage Temperature :** -4°F to 140°F (-20°C to 60°C)

Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.